



ACTION Safety

Premium nano-carbon
safety window films

LIFETIME WARRANTY

IR
69%

TSER
55%

UV
≥99%



Carbon window films are resistant to fading. Nano-carbon films use the smallest carbon particles available for the best clarity and haze reduction.

Drive assured with ACTION Safety, our series of safety-oriented window films.

Offered in 4-mil and 8-mil options,, ACTION Safety features shatterproof technology within its two-ply structure, effectively preventing broken-glass injuries. Combining unmatched glare reduction with our advanced nano-carbon technology, these films offer both top-notch protection and performance.



Safety First

From road accidents to smash-and-grabs, ACTION Safety has you covered. Our shatterproof technology effectively shields against broken-glass injuries, while its robust 2-ply structure dramatically increases the time needed to break through car windows.



Heat Reduction & Cooling Efficiency

ACTION Safety incorporates nano-carbon particles in its structure, allowing it to absorb heat and prevent it from reaching your vehicle interior. With an IR rejection rate of up to 69% and a TSER rate of up to 54%, the cooling efficiency is significantly improved, reducing air conditioner load and fuel consumption.



Privacy

The ACTION Safety series blocks up to 95% of visible light going through your vehicle, dramatically increasing passenger privacy.



Same as Heat Reduction & Cooling Effect

Glare negatively affects driving visibility, and the ACTION Safety series is able to reduce up to 93% of this glare. This ensures top-notch clarity, leading to less eye strain and a more focused drive.



UV Protection

Ultraviolet light from the sun can cause dangerous health conditions, including skin cancer. The ACTION Safety series blocks more than 99% of these harmful UV rays, providing long-term protection. It also preserves electronics, fabric, leather, and plastic, preventing fading and discoloration of your car interior.

		4 MIL				8 MIL		
		05	20	35	50	05	20	35
Visible Light Transmittance (VLT)		6%	20%	34%	45%	6%	20%	34%
Visible Light Reflectance (VLR)	Exterior	5%	5%	6%	6%	5%	5%	6%
	Interior	6%	6%	6%	7%	6%	6%	6%
Solar Energy	Transmittance	22%	30%	47%	55%	22%	35%	46%
	Reflectance	5%	5%	6%	7%	5%	5%	6%
	Absorbance	73%	65%	47%	38%	73%	60%	48%
IR Rejection	950 nm	69%	50%	41%	32%	68%	50%	38%
	1400 nm	55%	40%	32%	26%	54%	39%	29%
UV Rejection		≥99%	≥99%	≥99%	≥99%	≥99%	≥99%	≥99%
Glare Reduction		93%	80%	66%	55%	92%	79%	64%
Total Solar Energy Rejected (TSER)		54%	49%	38%	32%	54%	46%	39%
Shading Coefficient		0.51	0.57	0.7	0.76	0.51	0.54	0.69